Subsurface Sewage Treatment System Management Plan

Property Owner: Eric	c Schulz	_ Phone:		Date: 6/12/2019				
Tailing Address: 13836 Clare Downs Way City: Rosemount		semount MN	Zip:_55068					
Site Address: Near 19				Zip: 55760				
performance of your s must be performed by	will identify the operation and meptic system. Some of these activial licensed septic service provider	ties must be p	performed by you, the ho	meowner. Other tasks				
Local Government:	check every months. 2			needs to be checked months.				
	check every <u>36</u>	_ months.						
	sed on MN Rules Chapter 7080.2450, Subp	o. 2 & 3)						
	Nanagement Tasks – Check (look, listen) for leaks in to	oilate and drin	uning faucots Ponair loak	vs promptly				
	ing sewage – Regularly check for v	-	· -					
•	nt filter – Inspect and clean twice o		•	atment area.				
**	s – Alarm signals when there is a p	•		y time an alarm signals.				
	counter or water meter – Record y		·	,				
	-recommend meter readings be	conducted (ci	rcle one: <u>DAILY</u> <u>WE</u>	EKLY MONTHLY)				
	Management Tasks							
	Check to make sure tank is not l	_						
	Check and clean the in-tank effluent filter							
	Check the sludge/scum layer levels in all septic tanks							
	Recommend if tank should be p	umped						
	Check inlet and outlet baffles							
	Check the drainfield effluent lev	els in the rock	alayer					
	Check the pump and alarm syste	em functions						
	Check wiring for corrosion and f	unction						
	Check dissolved oxygen and efflor	uent tempera	ture in tank					
	Provide homeowner with list of	results and an	y action to be taken					
	Flush and clean laterals if cleance	outs exist						
Management Plan. If req	sponsibility to properly operate and muirements in the Management Plan aons. If I have a new system, I agree to	ire not met, I wi	ill promptly notify the perm	nitting authority and take				
Property Owner Signat	cure:		Date: _					
Docimor Cianatura	Oall Boulant		Data	6/12/2019				

See Reverse Side for Management Log

Maintenance Log

Activity		Date Accomplished								
Check frequently:										
Leaks: check for plumbing leaks										
Soil treatment area check for surfacing										
Lint filter: check, clean if needed										
Effluent screen: if owner-maintained										
Water usage rate (monitor frequency)										
Check annually:										
Caps: inspect, replace if needed										
Sludge & Scum/Pump										
Inlet & Outlet baffles										
Drainfield effluent leaks										
Pump, alarm, wiring										
Flush & clean laterals if cleanouts exists										
Other:	_									
Other:	_									
	•	•	•	•		•	•	•	•	

Notes: This is a Type III Septic System, Designer does not warranty or guaranty any part of this system.
Follow Operating permit requirements. Pump septic & pump tanks at least once every three years.
Check & Clean Effluent filter at least twice a year. Check all alarms at least once a year.
Mow Mound area at least once a year to keep trees and brush from growing in mound area.
No Traffic on mound area, No Snowmobiles, No ATV's, No Parking.
Mitigation/corrective action plan: