

Preliminary & Field Evaluation Form

www.SepticResource.com vers 12.4

Owner Information			
Date	<u>6/3/2020</u>	Sec / Twp / Rng	<u>S-10, T-46, R24</u>
Parcel ID	<u>17-0-012902</u>	LUG (county, city, township)	<u>Aitkin Co.</u>
Property Owner:	<u>Herbert Heldt</u>	Owners address (if different)	
Property Address:	<u>24716 Dam Lake Rd. Aitkin MN 56431</u>		
City / State / Zip:	_____		

Flow Information and Waste Type / Strength			
Estimated Design flow	<u>450</u>	Anticipated Waste strength	<input type="checkbox"/> Hi Strength <input checked="" type="checkbox"/> Domestic
Comments: Existing Septic System is failing		Any Non-Domestic Waste	<input type="checkbox"/> Yes (class V) <input checked="" type="checkbox"/> No
		Sewage ejector/grinder pump	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
		Water softener	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
		Garbage Disposal	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
		Daycare / In home business	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No

Site Information					
Existing & proposed lot improvements located (see site map)	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	Well casing depth	Existing deep well	
Easements on lot located (see site map)	<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No	Drainfield w/in 100' of residential well	<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No
Property lines determined (see site map) By Owner	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	Site w/in 200' of transient noncommunity water supply (TNCWS)	<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No
Req'd setbacks determined (see site map)	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	Site w/in an inner wellhead mgmt zone (CWS/NTNCWS)	<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No
Utilities located & identified (gopher state one call)	<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No	Buried water supply pipe w/in 50' of system	<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No
Access for system maintenance (shown on site map)	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	Site located in Shoreland (w/in 1000' of lake, 300' of river)	<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No
Soil treatment area protected	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	Site map prepared with previous items included	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
Construction related issues	_____				

Soil Information

		Evidence of site:	
		Cut	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
		Filled	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
		Compacted	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
		Disturbed	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Original soils	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	
Soil logs completed and attached	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	Perk test completed and attached (if applicable) <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Soil loading rate (gpd/ft ²)	<u>0.60</u>		Percolation rate (if applicable) _____
Depth/elev to SHWT	<u>13"</u>		Flooding or run-on potential (comments) <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Depth to system bottom maximum (or elev minimum)	<u>(+ 24")</u>		Flood elevation (if applicable) _____
Depth/elev to standing water (if applicable)	_____		Elevation of ordinary high water level (if applicable) _____
Depth/elev to bedrock (if applicable)	_____		Floodplain designation and elev - 100 yr/10 yr (if applicable) _____
Soil Survey information determined (see attachment)	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	
Differences between soil survey and field evaluation (if applicable)	_____ _____		

I hereby certify this evaluation was completed in accordance with MN 7080 and any local req's.



 Designer Signature

Brummer Septic LLC.

 Company

L-1347

 License #

Soil Observation Log

www.SepticResource.com vers 12.4

Owner Information	
Property Owner / project: <u>Herbert Heldt</u>	Date <u>6/3/2020</u>
Property Address / PID: <u>24716 Dam Lake Rd. Aitkin MN 564</u>	

Soil Survey Information	
<input type="checkbox"/> refer to attached soil survey	
Parent mat'l's:	<input checked="" type="checkbox"/> Till <input type="checkbox"/> Outwash <input type="checkbox"/> Lacustrine <input type="checkbox"/> Alluvium <input type="checkbox"/> Organic <input type="checkbox"/> Bedrock
landscape position:	<input type="checkbox"/> Summit <input type="checkbox"/> Shoulder <input checked="" type="checkbox"/> Side slope <input type="checkbox"/> Toe slope
soil survey map units:	<u>502 , 980</u> slope <u>3</u> % direction- <u>South</u>

Soil Log #1							
		<input checked="" type="checkbox"/> Boring <input type="checkbox"/> Pit	Elevation <u>97.7'</u>		Depth to SHWT <u>13"</u>		
Depth (in)	Texture	fragment %	matrix color	redox color	consistence	grade	shape
0 - 6	Topsoil Sandy Loam	<35	10YR3/2		Loose	Loose	Granular
6 - 13	Loam	<35	10YR4/4		Loose	Loose	Granular
13 - 18	Loam	<35	10YR4/4	7.5YR5/4	Loose	Loose	Granular
18 - 22	Clay Loam	<35			Friable	Weak	Blocky
		<35					

Comments:

24716 Dam Lake Rd. Aitkin MN 56431

Soil Log #2


		<input checked="" type="checkbox"/> Boring	<input type="checkbox"/> Pit	Elevation <u>97.9'</u>		Depth to SHWT <u>14"</u>	
Depth (in)	Texture	fragment %	matrix color	redox color	consistence	grade	shape
0 - 6	Topsoil Sandy Loam	<35	10YR3/2		Loose	Loose	Granular
6 - 14	Loam	<35	10YR4/4		Loose	Loose	Granular
14 - 18	Loam	<35	10YR4/4	7.5YR5/4	Loose	Loose	Granular
		<35			Loose	Loose	Granular
		<35			Loose	Loose	Granular

24716 Dam Lake Rd. Aitkin MN 56431

Soil Log #3

		<input checked="" type="checkbox"/> Boring	<input type="checkbox"/> Pit	Elevation <u>97.8'</u>		Depth to SHWT <u>14"</u>	
Depth (in)	Texture	fragment %	matrix color	redox color	consistence	grade	shape
0 - 6	Topsoil Sandy Loam	<35	10YR3/2		Loose	Loose	Granular
6 - 14	Loam	<35	10YR4/4		Loose	Loose	Granular
14 - 18	Loam	<35	10YR4/4	7.5YR5/4	Loose	Loose	Granular
		<35 35 - 50 >50			loose friable firm rigid	loose weak moderate strong	single grain granular blocky prismatic platy massive
		<35 35 - 50 >50			loose friable firm rigid	loose weak moderate strong	single grain granular blocky prismatic platy massive

I hereby certify this work was completed in accordance with MN 7080 and any local req's.


 Designer Signature

Brummer Septic LLC.
 Company

L-1347
 License #

Mound Design - Aitkin county

Property Owner: Herbert Heldt

Date: 6/3/2020

Site Address: 24716 Dam Lake Rd. Aitkin MN 56431

PID: 17-0-012902


Comments: _____

Instructions: = enter data = adjust if desired = computer calculated - DO NOT CHANGE!

- 1) bedroom Type Residential System
- 2) GPD design flow
- 3) Garbage disposal or pumped to septic Install 1650 Jacobson 2/compartment Tank Septic / pump
- 4) Gal Septic tank (code minimum) Gal Septic tank (design size / LUG req'd)
Tank options: none
- 5) GPD/ft² mound sand loading rate contour loading rate of req's a min ft. long rockbed
- 6) ft rockbed width ft rockbed length
- 7) ft lateral spacing ft perforation spacing (maximum of 3 for both)
 manifold connection
- 8) laterals feet long perfs / lateral perfs total
(1/2 a perf means the first perf starts at the middle feed manifold)
- 9) inch perfs at feet residual head gives gpm flow rate per perforation
for this perf size & spacing, & pipe size on line 12, max perfs/lateral = , line #8 must be less --> OK
- 10) doses per day (4 minimum)
- 11) gallons per dose (treatment volume) 1.50 5x
- 12) inch diameter laterals must be used to meet "4x pipe volume" requirement 2.00 3x
- 13) feet of inch supply line leads to gallons of drainback volume
(Tip: "top feed" manifold to control the drainback)
- 14) gallons TOTAL pump out volume (treatment + drainback)
- 15) feet vertical lift from pump to mound laterals, leads to a:
- 16) GPM @ feet of head, Pump requirement (note: >50gpm may require an extra 3-6' of head)
- 17) gal Dose tank (code minimum) gal Dose tank (design size / LUG req'd) at gpi
leads to a
- 18) inch swing on Demand float, or timed dosing of min ON (confirm pump rate with drawdown
(this delivers Average flow, =70% of Peak design flow) hrs OFF test and adjust as necessary)
- 19) inches from bottom of tank to "Pump OFF" float
- 20) inches from bottom of tank to "Pump ON" float, or inches to "Timer ON" float if time dosed
- 21) inches from bottom of tank to "Hi Level" float, or inches to "Hi Level" float if time dosed
- 22) gallons reserve capacity (after High Level Alarm is activated)

Electric Alarm on pump tank

- 23) gpd/ft² Absorption area Soil Loading Rate, which gives a mound ratio of (minimum)
 (this must match the soil boring log) desired mound ratio
- 24) percent site slope (0-20% range) (% downslope site slope, if different than upslope)
- 25) inches, or ft. to Redox or other limiting condition (need at least 12" to be a Type I)
 Treatment zone contains inches of 0% soil credit, and inches of 50% soil credit. Giving a:
- 26) inch, or ft. Sand Lift Mound **CRITICAL FOR FUTURE CERTIFICATIONS!!!**
- 27) ft. base absorption width (with sand beyond rockbed as follows):
 greater of: absorption width OR sand slope
- 28) ft. upslope and sideslope sand upslope
 ft. Downslope sand down slope
- Individual slope ratios give BERM widths (topsoil beyond rockbed) of:
- 29) upslope ratio ft. upslope berm
- 30) sideslope ft. sideslope berms
- 31) downslope ft. downslope berm
- 32) Overall Dimensions: ft. wide by ft. long Rock bed
 ft. wide by ft. long Mound footprint



Note:
 For 0 to 1% slopes, *Absorption Width* is measured from the *Bed* equally in both directions.
 For slopes >1%, *Absorption Width* is measured downhill from the upslope edge of the *Bed*.

- 33) Rock Bed:
 ft. by ft. by inches under pipe, plus 20% gives yd³ or *1.4= ton
- 34) Mound Sand: (note: volume is based on 3:1/4:1 slope from top of rockbed, Exchange sand for loamy cap if desired)
 up + downslope + ends + under rock = yd³ or *1.4= ton
 plus 20%
- 35) Loamy Cap:
 ft. by ft. 6" deep, plus 20% gives yd³ or *1.4= ton
- 36) Topsoil:
 ft. by ft. 6" deep, plus 20% gives yd³ or *1.4= ton

I hereby certify that I have completed this work in accordance with all applicable ordinances, rules and laws.

Designer Signature
 Company
 License#
 Date

INSPECTOR CHECKLIST - mound

24/16 Dam Lake Rd. AITKIN MN 56431

- WELL setbacks: 20' to pressure tested sewer line (5 psi for 15 min)
50' to everything 100' to dispersal area with shallow well
- PROPERTY LINES setback: 10' to everything
- Road setback: platted: 10' prop line. Metes & bounds: out of road easement, or outer ditch.
- LAKE / BLUFF setback: 20' for bluff. Lakes: GD ____, RD ____, NE _____. Protected wetland ____.
- Building setbacks: 10' for everything, 20' for dispersal area.
- WATER LINE under pressure sc 10' to bed, tank & sewer line. (else sewer line > 12" below, else ok w/pvc)

- Sewer line & baffle connection (no 90's, 3' between 45's, slope min 1" in 8', max 2" in 8')
(no depth req's, clean out every 100', Sch 40 pipe)

- Septic tank and risers (water tight, insulated, proper depth, existing verified by pumping)
mfg _____ 1120 gallons none _____

- Riser over outlet, riser over inlet or center, and 6"+ inspection pipe over any remaining baffles.
- No _____ effluent filter & alarm
- Dose tank risers and piping (water tight, insulated, proper depth, drainback)
mfg _____ 533 gallons

- dose pump _____ 27 gpm 23 head VERIFY PUMP CURVE 2.9 min ON 5.1 hr OFF

- float setting drop 6.2 inches at 12.7 gpi "DESIGNED" 4.1 inches approx float tether length
79.0 gal dose divided by _____ gpi "INSTALLED" = _____ inches float drop (field corrected)
LABEL pump requirements and drawdown on riser or panel

- Cam lock reachable from grade - 30" max. J-hook weep hole. Supply line access (no hard 90's)
2.0 inch supply pipe: Sch40, sloped 1/8"+, supported by 4" sch40 sleeve or compacted, and buried 6"+.
- splice box / control panel / electrical connections
- flow measurement: CT, ETM, time dosed, home water meter
- mound absorption area rough up
- mound rock dimensions 10.0 X 37.5
- Sand lift depth 24 inches. (Jar test : 2" sand leaves < 1/8" silt after 30 min)

- Absorption Sand beyond rock 10.7 upslope 15.0 downslope

- Bermed topsoil beyond rockbed 14 upslope 17 sideslope 20 downslope

- cover depth of 12-18"+ VERIFY
- 3 laterals (1-2' from edge of rock)
- 1.50 inch pipe size (Sch40 pipe & fittings)
- 3.0 ft lateral spacing

- 1/4" inch perforations
- 3.0 ft perforation spacing


- Air inlet at end of laterals, and at top feed manifold if necessary. VERIFY
- clean outs (no hard 90's)
- 4" inspection pipe to bottom of rock, anchored VERIFY

- Abandon existing system - if necessary Re-use existing tank certification
- monitoring plan and type _____
- well abandonment form - if necessary _____


System Elevations

Elv = 100' benchmark Nail on Tree East of mound.
 Top of Deep Well cap Elv. = 94.5'

(Grade elevations are existing. If a different final grade is desired it should be shown and described here.)




- 102' loamy cap
- 100.7' lateral
- 100' bottom rock
- 98' grade (at upslope rock bed)
- 13" SHWT (at upslope rock bed)



{ Design Drawing }

Property Owner: Herbert Heldt Date: 6/3/20 Designer's Initials: JB
 Parcel ID. Number: 17-0-012902 Address: 24716 Dam Lake Rd. Aitkin MN 56431
 one Inch = 40ft.



Top of deep well cap Elv. = 94.5'

	Surface/ SHWT	Nail on Tree = Bench Mark 100'		Existing Grade	
Soil Bore 1	97.7' / 13"	Bench Mark	100'		Upslope Edge of Rockbed Elv. = 98'
Soil Bore 2	97.9' / 14"	Ground Elv. BM	97.2'		Bottom of Rockbed Elv. = 100'
Soil Bore 3	97.8' / 14"	Ground Elv. Tank	95'	New	Top of Washed Sand Elv. = 100'
	Ground at	Proposed house	96.7'	SW corner	Elv. Of Sewer pipe at Cabin Elv. = 95.7'

Please show all that apply (Existing)

- Wells within 100ft. Of Drain field.
- Water lines within 10 ft. of Drain field.
- Drain field Areas:

Please Draw to Scale with North to Top or Left Side of Page:

- | | |
|---------------------------|-----------------------------------|
| Disturbed/Compacted Areas | Access Route for Tank Maintenance |
| Component Location | Property Lines |
| OHW ordinary high water | Structures |
| Lot Easements | Setbacks |

Mound Design Notes - Aitkin county

Property Owner: Herbert Heldt

Date: 6/3/20

Site Address: 24716 Dam Lake Rd. Aitkin MN 56431

PID: 17-0-012902

Comments: **Mound design may not follow Aitkin co. Auto fill form for mound design.**

- 1 This is a type I mound for a 3 bedroom House. Existing deep well location is NE of House.
- 2 Existing Septic system is failing. Pump collapse and fill existing tank, abandon drainfield.
- 3 Mound and tank meet setbacks to property lines + 20' in any direction.
- 4 Bench Mark Elevation is a nail on a tree near East end of mound area Elv.= 100'.
- 5 Install Jacobson 1650 Compartment tank for gravity flow from house.
Install clean-out near house and install new 4" sewer pipe to tank, (existing was home owner installed)
- 6 Elevation contour of rock bed upslope edge is 98'.
The area size of the rock bed is 10' x 38' . Absorption area is 38' x 35.7'.
Sand absorption area is 10.7 ft. up slope + 10 ft. rockbed + 15 ft. downslope = approx. 35.7 ft. wide sand base.
Berms are 14ft. Upslope, 20ft. Down slope, 10ft. Rock bed = approx. 44ft. Wide.
Overall mound size is approx. 44' wide x 72' long and approx. 4' high. End Berms are 17 ft wide.
- 7 The bench mark is the nail on the tree near mound area, BM = Elv. 100'.
Installer to double check bench mark. Installer should confirm bench mark and sand height Elv. with inspector.
Installer should record bench mark Elv. and sand height on installation inspection form.
- 8 The top of the washed sand and bottom of rock bed is Elv. 100'.
It is important that the soils do not get compacted, and that clean washed sand is used.
- 9 The Jacobson 1650 compartment tank will be gravity flow from dwelling. Install the pump for 7 demand doses per day. approx. 79 gallons per dose, 6.2 inches of tank level. Install alarm at 3 inches from pump on level.
Install all manholes, inspection pipes and clean-outs to grade or above, insulate top of tank.
- 10 Install a 2" supply pipe from tank to end manifold in rock bed, install so pipe drains back to tank.
Install 1.5" laterals with 9" of rock under them. (Install Lateral clean-outs at far end of laterals. Recommended)
Drill 1/4" holes for Perf sizing, 36" on centers.
Install 4" inspection pipe to bottom of rock bed, secure in rock bed and raise to above final grade.

Designed to Aitkin Co. and MPCA recommendations and requirements.




Designer Signature

Brummer Septic LLC.
Design Company

L-1347
License#

1650 Gallon 2 Compartment Septic Tank


TOP VIEW



$533 / 42" = 12.69 \text{ GPI}$

SIDE VIEW

Drawings Owned BY Jacobson Precast, Inc.
36641 HWY 169, Aitkin, Mn 56431



Detailed Parcel Report

Parcel Number: 17-0-012902

General Information

Township/City:	LEE TOWNSHIP	Lake Number:	0
Taxpayer Name:	HELDT, HERBERT A	Lake Name:	
Taxpayer Address:	24716 DAM LAKE ST	Acres:	23.92
	MCGREGOR MN 55760	School District:	4.00
Property Address:	24716 Dam Lake St		
Township:	46		
Range:	24		
Section:	10		
Green Acres:	No		
Plat:			
Brief Legal Description:	W 1/2 OF SW 1/4 OF SE SW & E 1/2 OF SW SW LESS 1.08 AC HWY		

Tax Information


Class Code 1:	Residential 1 unit
Class Code 2:	Rural Vacant Land
Class Code 3:	Unclassified
Homestead:	Owner Homestead
Assessment Year:	2020

Estimated Land Value:	\$45,800.00
Estimated Building Value:	\$47,300.00
Estimated Total Value:	<u>\$93,100.00</u>
Prior Year Total Taxable Value:	\$62,620.00
Current Year Net Tax (Specials Not Included):	\$510.00
Total Special Assessments:	\$0.00
**Current Year Balance Not Including Penalty:	\$255.00
Delinquent Taxes:	No

* For more information on delinquent taxes, please call the Aitkin County Treasurer's Office at 218-927-7325.

** Balance Due on a parcel does not include late payment penalties.

Soil Map—Aitkin County, Minnesota
(Heldt)



Map Scale: 1:1,500 if printed on A portrait (8.5" x 11") sheet.



Map projection: Web Mercator Corner coordinates: WGS84 Edge ticks: UTM Zone 15N WGS84



Natural Resources
Conservation Service

Web Soil Survey
National Cooperative Soil Survey

6/5/2020

Aitkin County, Minnesota

502—Dusler silt loam

Map Unit Setting

National map unit symbol: gjh6
Elevation: 980 to 1,640 feet
Mean annual precipitation: 25 to 30 inches
Mean annual air temperature: 39 to 45 degrees F
Frost-free period: 120 to 140 days
Farmland classification: Prime farmland if drained

Map Unit Composition

Dusler and similar soils: 85 percent
Minor components: 15 percent
Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Dusler

Setting

Landform: Moraines
Landform position (two-dimensional): Footslope
Down-slope shape: Linear
Across-slope shape: Concave
Parent material: Loamy till

Typical profile

A - 0 to 5 inches: silt loam
Eg, 2B/E - 5 to 21 inches: fine sandy loam
2Bt1, 2Bt2 - 21 to 50 inches: clay loam
2C - 50 to 60 inches: loam

Properties and qualities

Slope: 0 to 2 percent
Depth to restrictive feature: More than 80 inches
Natural drainage class: Somewhat poorly drained
Capacity of the most limiting layer to transmit water (Ksat):
 Moderately low to moderately high (0.06 to 0.20 in/hr)
Depth to water table: About 6 inches
Frequency of flooding: None
Frequency of ponding: None
Calcium carbonate, maximum in profile: 5 percent
Available water storage in profile: High (about 10.4 inches)

Interpretive groups

Land capability classification (irrigated): None specified
Land capability classification (nonirrigated): 2w
Hydrologic Soil Group: C/D
Forage suitability group: Level Swale, Acid (G090AN005MN)
Hydric soil rating: No

Minor Components

Duluth and similar soils

Percent of map unit: 7 percent

Hydric soil rating: No

Blackhoof and similar soils

Percent of map unit: 4 percent

Landform: Depressions

Hydric soil rating: Yes

Mahtowa and similar soils

Percent of map unit: 4 percent

Landform: Swales

Hydric soil rating: Yes

Data Source Information

Soil Survey Area: Aitkin County, Minnesota

Survey Area Data: Version 20, Sep 16, 2019

Aitkin County, Minnesota

980—Blackhoof and Mahtowa soils

Map Unit Setting

National map unit symbol: gjk7
Elevation: 980 to 1,640 feet
Mean annual precipitation: 25 to 30 inches
Mean annual air temperature: 39 to 45 degrees F
Frost-free period: 120 to 140 days
Farmland classification: Not prime farmland

Map Unit Composition

Mahtowa and similar soils: 45 percent
Blackhoof and similar soils: 45 percent
Minor components: 10 percent
Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Mahtowa

Setting

Landform: Depressions on moraines
Down-slope shape: Concave
Across-slope shape: Concave
Parent material: Loamy till

Typical profile

Oa - 0 to 3 inches: muck
A - 3 to 11 inches: loam
Bg,C - 11 to 60 inches: loam

Properties and qualities

Slope: 0 to 1 percent
Depth to restrictive feature: More than 80 inches
Natural drainage class: Very poorly drained
Capacity of the most limiting layer to transmit water (Ksat):
Moderately high (0.20 to 0.60 in/hr)
Depth to water table: About 0 inches
Frequency of flooding: None
Frequency of ponding: Frequent
Available water storage in profile: High (about 11.6 inches)

Interpretive groups

Land capability classification (irrigated): None specified
Land capability classification (nonirrigated): 5w
Hydrologic Soil Group: C/D
Forage suitability group: Organic (G090AN014MN)
Hydric soil rating: Yes

Description of Blackhoof

Setting

Landform: Depressions on moraines
Down-slope shape: Concave
Across-slope shape: Concave
Parent material: Organic material over loamy till

Typical profile

Oa - 0 to 10 inches: muck
A - 10 to 14 inches: clay loam
Bg,C - 14 to 60 inches: loam

Properties and qualities

Slope: 0 to 1 percent
Depth to restrictive feature: More than 80 inches
Natural drainage class: Very poorly drained
Capacity of the most limiting layer to transmit water (Ksat):
Moderately low to moderately high (0.06 to 0.20 in/hr)
Depth to water table: About 0 inches
Frequency of flooding: None
Frequency of ponding: Frequent
Calcium carbonate, maximum in profile: 5 percent
Available water storage in profile: Very high (about 14.0 inches)

Interpretive groups

Land capability classification (irrigated): None specified
Land capability classification (nonirrigated): 6w
Hydrologic Soil Group: C/D
Forage suitability group: Organic (G090AN014MN)
Hydric soil rating: Yes

Minor Components

Seelyeville and similar soils

Percent of map unit: 4 percent
Landform: Bogs
Hydric soil rating: Yes

Stones on the surface

Percent of map unit: 3 percent
Landform: Swales
Hydric soil rating: Yes

Dusler and similar soils

Percent of map unit: 3 percent
Hydric soil rating: No

Data Source Information

Soil Survey Area: Aitkin County, Minnesota
Survey Area Data: Version 20, Sep 16, 2019