

FIELD EVALUATION SHEET

PRELIMINARY EVALUATION DATE 6-7-2020, FIELD EVALUATION DATE 6-7-20
 PROPERTY OWNER: Tim Patterson PHONE 952-826-9480
 ADDRESS: 29652 335th Lane CITY, STATE, ZIP: Aitkin, Mn 56431
 LEGAL DESCRIPTION:
 PIN# 09-0-002310 SEC T R TWP NAME
 FIRE# Lake LAKE/RIVER Damn Lake LAKE CLASS Rd OHWL FT.

DESCRIPTION OF SOIL TREATMENT AREAS

	AREA #1	AREA #2	REFERENCE BM ELEV. _____ FT. REFERENCE BM DESCRIPTION _____
DISTURBED AREAS	YES <u> </u> NO <u>X</u>	YES <u> </u> NO <u> </u>	_____
COMPACTED AREAS	YES <u> </u> NO <u>X</u>	YES <u> </u> NO <u> </u>	_____
FLOODING	YES <u> </u> NO <u>X</u>	YES <u> </u> NO <u> </u>	_____
RUN ON POTENTIAL	YES <u> </u> NO <u>X</u>	YES <u> </u> NO <u> </u>	_____
SLOPE %	<u>Flat 0%</u>	_____	_____
DIRECTION OF SLOPE	_____	_____	_____
LANDSCAPE POSITION	<u>Backyard</u>	_____	_____
VEGETATION TYPES	<u>Grass - Existing mound</u>	_____	_____

DEPTH TO STANDING WATER OR MOTTLED SOIL: BORING#1 6", 1A 6", 2 , 2A

BOTTOM ELEVATION-FIRST TRENCH OR BOTTOM OF ROCK BED: #1 105 FT., #2 105 FT.

SOIL SIZING FACTOR: SITE #1 1.27, SITE #2

CONSTRUCTION RELATED ISSUES: Mound Failed Compliance - needs a "Other" system

LIC# 1054 SITE EVALUATOR SIGNATURE: Tom Antonsen

SITE EVALUATOR NAME: Tom Antonsen TELEPHONE# 318-851-7757

LUG REVIEW _____ DATE 6-14-2020

Comments: _____

SOIL BORING LOGS ON REVERSE SIDE

SOILS CHARTS FOR BOTH PROPOSED AND ALTERNATE SITES

1 (PROPOSED) SOILS DATA

DEPTH (INCHES)	TEXTURE	MUNSELL COLOR
5"	loamy sand	3/2 top soil
5-12"	sandy loam	loam 5/3
		standing water @ 9"

2 (PROPOSED) SOILS DATA

DEPTH (INCHES)	TEXTURE	MUNSELL COLOR
6"	top soil	loam 3/2
6-12"	sandy loam	loam 5/3
		standing water at 8-9"

1 (ALTERNATE) SOILS DATA

DEPTH (INCHES)	TEXTURE	MUNSELL COLOR

2 (ALTERNATE) SOILS DATA

DEPTH (INCHES)	TEXTURE	MUNSELL COLOR

ADDITIONAL SOIL BORINGS MAY BE REQUIRED

MOUND DESIGN WORK SHEET (For Flows up to 1200 gpd)

A. Average Design FLOW

Estimated 450 gpd (see figure A-1)
or measured _____ x 1.5 (safety factor) = _____ gpd

B. SEPTIC TANK Capacity

Existing 1350 Compartment tank
gallons (see figure C-1)

C. SOILS (refer to site evaluation)

1. Depth to restricting layer = 6" feet
2. Depth of percolation tests = — feet
3. Texture Sandy Loam
Percolation rate 1.27 mpi
4. Soil loading rate 1.50 gpd/sqft (see figure D-33)
5. Percent land slope 0 %

A-1: Estimated Sewage Flows in Gallons per Day

number of bedrooms	Class I	Class II	Class III	Class IV 60% of the values in the Class I, II, or III columns.
2	300	225	180	
3	450	300	218	
4	600	375	256	
5	750	450	294	
6	900	525	332	
7	1050	600	370	
8	1200	675	408	

C-1: Septic Tank Capacities (in gallons)

Number of Bedrooms	Minimum Liquid Capacity	Liquid capacity with garbage disposal	Liquid capacity with disposal & lift inside
2 or less	750	1125	1500
3 or 4	1000	1500	2000
5 or 6	1500	2250	3000
7, 8 or 9	2000	3000	4000

D. ROCK LAYER DIMENSIONS

1. Multiply average design flow (A) by 0.83 to obtain required rock layer area.

$$450 \text{ gpd} \times 0.83 \text{ sqft/gpd} = 373.5 \text{ sqft}$$

2. Determine rock layer width = 0.83 sqft/gpd x linear Loading Rate (LLR)

$$0.83 \text{ sqft/gpd} \times \text{LLR} = 10 \text{ ft}$$

3. Length of rock layer = area ÷ width =

$$373.5 \text{ sqft (D1)} \div 10 \text{ ft (D2)} = 38 \text{ ft}$$

E. ROCK VOLUME

$$10 \times 38 \text{ Bed}$$

Mound LLR

< 120 MPI	≤ 12
$\geq 120 \text{ MPI}$	≤ 6

1. Multiply rock area (D1) by rock depth of 1 ft to get cubic feet of rock

$$373.5 \text{ sqft} \times 1 \text{ ft} = 373.5 \text{ cuft}$$

2. Divide cuft by 27 cuft/cuyd to get cubic yards

$$373.5 \text{ cuft} \div 27 \text{ cuyd/cuft} = 14.07 \text{ cuyd}$$

3. Multiply cubic yards by 1.4 to get weight of rock in tons

$$14.07 \text{ cuyd} \times 1.4 \text{ ton/cuyd} = 19.7 \text{ tons}$$

F. SEWAGE ABSORPTION WIDTH

Absorption width equals absorption ratio (See Figure D-33)
times rock layer width (D2)

$$1.50 \times 10 \text{ ft} = 15 \text{ ft}$$

D-33: Absorption Width Sizing Table

Percolation Rate in Minutes per Inch (MPI)	Soil Texture	Loading Rate Gallons per day per square foot	Absorption Ratio
Faster than 5	Coarse Sand Medium Sand Loamy Sand Fine Sand	1.20	1.00
6 to 15	Sandy Loam	0.79	1.50
16 to 30	Loam	0.60	2.00
31 to 45	Silt Loam	0.50	2.40
46 to 60	Sandy Clay Loam Silty Clay Loam Clay Loam	0.45	2.67
61 to 120	Silty Clay Sandy Clay Clay	0.24	5.00
Slower than 120*			

*System designed for these soils must be other or performance

G. MOUND SLOPE WIDTH & LENGTH

(landslope greater than 1%)

1. Downslope absorption width = absorption width (F) minus rock layer width (D2)

$$15 \text{ ft} - 10 \text{ ft} = 5 \text{ ft}$$

2. Calculate mound size

UPSLOPE

- a. Depth of clean sand fill at upslope edge of rock layer = 3 ft minus the distance to restricting layer (C1)

$$3 \text{ ft} - 0 \text{ ft} = 3 \text{ ft}$$

- b. Mound height at the upslope edge of rock layer = depth of clean sand for separation (G2a) at upslope edge plus depth of rock layer (1 ft) plus depth of cover (1 ft)

$$3 \text{ ft} + 1 \text{ ft} + 1 \text{ ft} = 5 \text{ ft}$$

- c. Upslope berm multiplier based on land slope $\frac{3}{5}$ (see figure D-34)

- d. Upslope width = berm multiplier (G2c) x upslope mound height (G2b):

$$3 \times 5 \text{ ft} = 15 \text{ ft}$$

DOWNSLOPE

- e. Drop in elevation = rock layer width (D2) x percent landslope (C5) $\div 100$

$$0 \text{ ft} \times 0 \% \div 100 = 0 \text{ ft}$$

- f. Downslope mound height = depth of clean sand for slope difference (G2e) at downslope rock edge plus the mound height at the upslope edge of rock layer (G2b)

$$0 \text{ ft} + 5 \text{ ft} = 5 \text{ ft}$$

- g. Downslope berm multiplier based on percent land slc $\frac{3}{5}$ (see figure D-34)

- h. Downslope width = downslope multiplier (G2g) times downslope mound height (G2f)

$$3 \times 5 \text{ ft} = 15 \text{ ft}$$

- i. Select the greater of G1 and G2h as the downslope width: 15 ft


- j. Total mound width is the sum of upslope width (G2d) width plus rock layer width (D2) plus downslope width (G2i)

$$15 \text{ ft} + 10 \text{ ft} + 15 \text{ ft} = 40 \text{ ft}$$

- k. Total mound length is the sum of upslope width (G2d) plus rock layer length (D3) plus upslope width (G2d)


$$15 \text{ ft} + 38 \text{ ft} + 15 \text{ ft} = 68 \text{ feet}$$

Landslope > 1% slope



D-34: SLOPE MULTIPLIER TABLE


Land Slope, in %	UPSLOPE multipliers for various slope ratios						DOWNSLOPE multipliers for various slope ratios				
	3:1	4:1	5:1	6:1	7:1	8:1	3:1	4:1	5:1	6:1	7:1
0	3.0	4.0	5.0	6.0	7.0	8.0	3.0	4.0	5.0	6.0	7.0
1	2.91	3.85	4.76	5.66	6.54	7.41	3.09	4.17	5.26	6.38	7.53
2	2.83	3.70	4.54	5.36	6.14	6.90	3.19	4.35	5.56	6.82	8.14
3	2.75	3.57	4.35	5.08	5.79	6.45	3.30	4.54	5.88	7.32	8.86
4	2.69	3.45	4.17	4.84	5.46	6.06	3.41	4.76	6.25	7.89	9.72
5	2.61	3.33	4.00	4.62	5.19	5.71	3.53	5.00	6.67	8.57	10.77
6	2.54	3.23	3.85	4.41	4.93	5.41	3.66	5.26	7.14	9.38	12.07
7	2.48	3.12	3.70	4.23	4.70	5.13	3.80	5.56	7.69	10.34	13.73
8	2.42	3.03	3.57	4.05	4.49	4.88	3.95	5.88	8.33	11.54	15.91
9	2.36	2.94	3.45	3.90	4.30	4.65	4.11	6.25	9.09	13.04	18.92
10	2.31	2.86	3.33	3.75	4.12	4.44	4.29	6.67	10.00	15.00	23.33
11	2.26	2.78	3.23	3.61	3.95	4.26	4.48	7.14	11.11	17.65	30.43
12	2.21	2.70	3.12	3.49	3.80	4.08	4.69	7.69	12.50	21.43	43.75



Final Dimensions:



$$40 \times 68$$

I hereby certify that I have completed this work in accordance with applicable ordinances, rules and laws.

 (signature)

1054 (license #)

6-14-20 (date)



Total Length
(E6) 65'

Mound is 40x68 - 3.0 slopes

PRESSURE DISTRIBUTION SYSTEM

1. Select number of perforated laterals 3

2. Select perforation spacing = 2.5 ft

3. Since perforations should not be placed closer than 1 foot to the edge of the rock layer (see diagram), subtract 2 feet from the rock layer length.

$$\frac{38}{\text{Rock layer length}} - 2 \text{ ft} = \underline{36} \text{ ft}$$

4. Determine the number of spaces between perforations. Divide the length (3) by perforation spacing (2) and round down to nearest whole number.

$$\text{Perforation spacing} = \underline{38} \text{ ft} \div \underline{2.5} \text{ ft} = \underline{14} \text{ spaces}$$

5. Number of perforations is equal to one plus the number of perforation spaces (4). Check figure E-4 to assure the number of perforations per lateral guarantees <10% discharge variation.

$$\underline{14} \text{ spaces} + 1 = \underline{15} \text{ perforations/lateral}$$

6. A. Total number of perforations = perforations per lateral (5) times number of laterals (1)

$$\underline{15} \text{ perfs/lat} \times \underline{3} \text{ lat} = \underline{45} \text{ perforations}$$

B. Calculate the square footage per perforation.

Should be 6-10 sqft/perf. Does not apply to at-grades.

Rock bed area = rock width (ft) x rock length (ft)

$$\underline{10} \text{ ft} \times \underline{38} \text{ ft} = \underline{380} \text{ sqft}$$

Square foot per perforation = Rock bed area ÷ number of perfs (6)


$$\underline{380} \text{ sqft} \div \underline{45} \text{ perfs} = \underline{8.4} \text{ sqft/perf}$$

7. Determine required flow rate by multiplying the total number of perforations (6A) by flow per perforation (see figure E-6)

$$\underline{45} \text{ perfs} \times \underline{.74} \text{ gpm/perf} = \underline{33.3} \text{ gpm}$$

8. If laterals are connected to header pipe as shown on upper example, to select minimum required lateral diameter; enter figure E-4 with perforation spacing (2) and number of perforations per lateral (5). Select minimum diameter for perforated lateral = 1.5 inches.

9. If perforated lateral system is attached to manifold pipe near the center, lower diagram, perforated lateral length (3) and number of perforations per lateral (5) will be approximately one half of that in step 8. Using these values, select minimum diameter for perforated lateral = _____ inches.



Perf Sizing 3/16" - 1/4"
Perf Spacing 1.5'- 5'

E-4: Maximum allowable number of 1/4-inch perforations per lateral to guarantee <10% discharge variation

perforation spacing (feet)	1 inch	1.25 inch	1.5 inch	2.0 inch
2.5	8	14	18	28
3.0	8	13	17	26
3.3	7	12	16	25
4.0	7	11	15	23
5.0	6	10	14	22


E-6: Perforation Discharge in gpm

head (feet)	perforation diameter (inches)			
	1/8	3/16	7/32	1/4
1.0 ^a	0.18	0.42	0.56	0.74
2.0 ^b	0.26	0.59	0.80	1.04
5.0	0.41	0.94	1.26	1.65


^a Use 1.0 foot for single-family homes.

^b Use 2.0 feet for anything else.

MANIFOLD LOCATED AT END OF PRESSURE DISTRIBUTION SYSTEM



LAYOUT OF PERFORATED PIPE LATERALS FOR PRESSURE DISTRIBUTION IN MOUND



I hereby certify that I have completed this work in accordance with applicable ordinances, rules and laws.

(signature)

1054 (license #)

6-14-20 (date)

PUMP SELECTION PROCEDURE

1. Determine pump capacity:

A. Gravity distribution

1. Minimum required discharge is 10 gpm
2. Maximum suggested discharge is 45 gpm. For other establishments at least 10% greater than the water supply rate, but no faster than the rate at which effluent will flow out of the distribution device.

B. Pressure distribution

See pressure distribution work sheet

From A or B Selected pump capacity: 33.3 gpm

2. Determine pump head requirements:

A. Elevation difference between pump and point of discharge?

9 feet

B. Special head requirement? (See Figure at right - Special Head Requirements)

5 feet

C. Calculate Friction loss

1. Select pipe diameter 2" in

2. Enter Figure E-9 with gpm (1A or B) and pipe diameter (C1).

Read friction loss in feet per 100 feet from Figure E-9

Friction Loss = 2.06 ft/100ft of pipe

3. Determine total pipe length from pump discharge to soil treatment discharge point. Estimate by adding 25 percent to pipe length for fitting loss. Total pipe length times 1.25 = equivalent pipe length

50 feet x 1.25 = 62.5 feet

4. Calculate total friction loss by multiplying friction loss (C2)

in ft/100 ft by the equivalent pipe length (C3) and divide by 100.

= 2.06 ft/100ft x 62.5 ÷ 100 = 1.3 ft


D. Total head required is the sum of elevation difference (A), special head requirements (B), and total friction loss (C4)

9 ft + 5 ft + 1.3 ft =

Total head: 15.3 feet

3. Pump selection

A pump must be selected to deliver at least 33.3 gpm
(1A or B) with at least 15.3 feet of total head (2D)



Special Head Requirements		
Gravity Distribution	0 ft	
Pressure Distribution	5 ft	

E-9: Friction Loss in Plastic Pipe Per 100 feet			
flow rate gpm	nominal pipe diameter 1.5"	2"	3"
20	2.47	0.73	0.11
25	3.73	1.11	0.16
30	5.23	1.55	0.23
35	6.96	2.06	0.30
40	8.91	2.64	0.39
45	11.07	3.28	0.48
50	13.46	3.99	0.58
55		4.76	0.70
60		5.60	0.82
65		6.48	0.95
70		7.44	1.09

152 Zoehlert

I hereby certify that I have completed this work in accordance with applicable ordinances, rules and laws.

Tom Johnson (signature) 1054 (license #) 614-20 (date)

DOSING CHAMBER SIZING

1. Determine area

A. Rectangle area = $L \times W$


$\underline{\quad} \times \underline{\quad} = \underline{\quad}$ square feet

B. Circle area = $\pi (3.14) \times \text{radius in feet} \times \text{radius in feet}$

$3.14 \times \underline{\quad} \text{ft} \times \underline{\quad} \text{ft} = \underline{\quad} \text{sqft}$

C. Get area from manufacturer $\underline{\quad} \text{sqft}$

USE 500 gallon
Lift tank



2. Calculate gallons per inch

There are 7.5 gallons per cubic foot of volume, therefore multiply the area (1A, B or C) times the conversion factor and divide by 12 inches per foot to calculate gallon per inch.
Area $\times 7.5 \div 12 = \underline{\quad} \text{sqft} \times 7.5 \div 12 \text{ in/ft} = \underline{\quad} \text{gallon per inch}$

3. Calculate total tank volume

A. Depth from bottom of inlet pipe to tank bottom $\underline{\quad}$ in

B. Total tank volume = depth from bottom of inlet pipe to tank bottom (3A) \times gal/in (2)
 $= \underline{\quad} \text{in} \times \underline{\quad} \text{gal/in} = \underline{\quad} \text{gal}$

4. Calculate gallons to cover pump (with 2-3 inches of water covering pump)

(Pump and block height (inch) + 2 inch) \times gallon/inch

$(\underline{\quad} \text{in} + 2 \text{ in}) \times \underline{\quad} \text{gal/in} = \underline{\quad} \text{gallon}$

5. Calculate total pumpout volume

A. Select pump size for 4-5 doses per day. Gallon per dose = gpd (see figure A-1)
 $/ \text{doses per day} = \underline{500} \text{ gpd} \div \underline{4} \text{ doses/day} = \underline{125} \text{ gallons}$

B. Calculate drainback

1. Determine total pipe length, 50 feet

2. Determine liquid volume of pipe, .17 gal per ft (see figure E-20)

3. Drainback quantity = 50 ft (5B1) \times .17 gal per ft (5B2) = 8.5 gal

C. Total pump out volume = dose volume (5A) + drainback (5B3)

125 gal + 8.5 gal = 131 Total gallon

6. Float separation distance (using total pumpout volume)

Total pumpout volume (5C) \div gal/inch (2)

131 gal \div 14.13 gal/in = 8.5 inch

7. Calculate volume for alarm (typically 2 to 3 inches)

Alarm depth (inch) \times gallon/inch (2) = $\underline{\quad} \text{in} \times \underline{\quad} \text{gal/in} = \underline{\quad} \text{gal}$

Set Alarm float
3" higher than
Pump float

8. Calculate total gallon = gallons over pump (4) + gallons pumpout (5C) + gallons alarm (7)

131 gal + 8.5 gal + 8.5 gal = 148 gallons

9. Total Tank Depth = total gallon (8) \div gallon/inch (2)

148 gal \div 14.13 gal/in = 10.5 in

Recommended:

Calculate reserve capacity (75% the daily flow)

Daily flow $\times .75 = \underline{450} \times .75 = \underline{337.5}$ gallons


I hereby certify that I have completed this work in accordance with applicable ordinances, rules and laws.

Tom Sennott (signature)

1054

(license #)


6-14-20 (date)



Legal Tank:
500 gallons or
100% the Daily flow
or
Alternating Pumps

A-1: Estimated Sewage Flows in Gallons per Day				
number of bedrooms	Class I	Class II	Class III	Class IV
2	300	225	180	60%
3	450	300	218	of the values
4	600	375	256	in the
5	750	450	294	columns
6	900	525	332	Class I,
7	1050	600	370	II, or III
8	1200	675	408	columns.

Pipe Diameter inches	Gallons per foot
1	0.045
1.25	0.078
1.5	0.11
2	0.17
2.5	0.25
3	0.38
4	0.66




CLIENT: Tim Patterson

SKETCH SHEET

DATE: 6-14-20

MAP DRAWN TO SCALE WITH A NORTH ARROW



CHECK OFF LIST--HAVE ALL OF THE FOLLOWING BEEN DRAWN ON THE MAP??

SHOW EXISTING OR PROPOSED

- WATER WELLS WITHIN 100 FT OF TREATMENT AREAS
- PRESSURE WATER LINES WITHIN 10 FT OF TREATMENT AREAS
- STRUCTURES
- LOT IMPROVEMENTS
- ALL SOIL TREATMENT AREAS
- ALL ISTM COMPONENTS
- HORIZONTAL AND VERTICAL REFERENCE
- POINT OF SOIL BORINGS
- DIRECTION OF SLOPE
- LOT EASEMENTS
- ALL LOT DIMENSIONS
- DISTURBED/COMPACTED AREAS
- SITE PROTECTION-LATHE AND RIBBON EVERY 15 FT
- ACCESS ROUTE FOR TANK MAINTENANCE

REQUIRED SETBACKS

- STRUCTURES
- PROPERTY LINES
- OHWL

COMMENTS:

DESIGNER SIGNATURE

LICENSE# 1054

INDICATE ELEVATIONS

BENCHMARK Lake = 100

ELEVATION OF SEWER LINE @ HOUSE 101

ELEVATION @ TANK INLET 100

ELEVATION @ BOTTOM OF ROCK LAYER 105

ELEVATION @ BOTTOM OF BORING OR RESTRICTIVE LAYER 101.5

ELEVATION OF PUMP 95

ELEVATION OF DISTRIBUTION DEVICE 105.5

DATE 6-14-20