

FIELD EVALUATION SHEET

PRELIMINARY EVALUATION DATE 5-25-23, FIELD EVALUATION DATE 5-25-23
PROPERTY OWNER: Joe Baker / Scott + Virginia Ok phone
ADDRESS: 38588 Hwy 47 CITY, STATE, ZIP: Aitken Mn 56431
LEGAL DESCRIPTION:
PIN# 31-0-057101 SEC 29 T 47 R 26 TWP NAME Spencer
FIRE# _____ LAKE/RIVER _____ LAKE CLASS _____ OHWL _____ FT. _____

DESCRIPTION OF SOIL TREATMENT AREAS

	AREA #1	AREA #2	REFERENCE BM ELEV. <u>100</u> FT.
DISTURBED AREAS	YES _____ NO <u>X</u>	YES _____ NO _____	REFERENCE BM DESCRIPTION _____
COMPACTED AREAS	YES _____ NO <u>X</u>	YES _____ NO _____	_____
FLOODING	YES _____ NO <u>X</u>	YES _____ NO _____	_____
RUN ON POTENTIAL	YES _____ NO <u>X</u>	YES _____ NO _____	_____
SLOPE %	<u>2</u>	_____	_____
DIRECTION OF SLOPE	_____	_____	_____
LANDSCAPE POSITION	<u>side slope</u>	_____	_____
VEGETATION TYPES	<u>pine trees</u>	_____	_____

DEPTH TO STANDING WATER OR MOTTLED SOIL: BORING# 1 1', 1A _____, 2 _____, 2A _____

BOTTOM ELEVATION--FIRST TRENCH OR BOTTOM OF ROCK BED: #1 _____ FT., #2 _____ FT.

SOIL SIZING FACTOR: SITE #1 2.2, SITE #2 _____

CONSTRUCTION RELATED ISSUES: elevations to be determined by new plumbing

LIC# 2264 SITE EVALUATOR SIGNATURE: Lou Ann Maschler

SITE EVALUATOR NAME: Lou Ann Maschler TELEPHONE# 218-839-3042

LUG REVIEW _____ DATE _____

Comments: replace cesspool with conforming mound system

SOIL BORING LOGS ON REVERSE SIDE

DESCRIPTION FOR OKESON

Parcel I

The Southeast Quarter of the Southwest Quarter of Section 29, Township 47, Range 26.

Except that part of the Southeast Quarter of the Southwest Quarter platted as Spencer Cemetery, as more particularly appears in the plat thereof on file and of record in the office of the register of deeds of Aitkin County, Minnesota.

Aitkin County, Minnesota.
(Abstract)

Parcel II (remnant)

The Southwest Quarter of the Southeast Quarter and the Northwest Quarter of the Southeast Quarter of Section 29, Township 47, Range 26.

AND

The South Two (2) rods of the Southwest Quarter of the Northeast Quarter of Section 29, Township 47, Range 26, subject to mineral reservations, easements, zoning ordinances and restrictions of record, as shown by instrument recorded as Document No. 157397 in the Office of the Aitkin County Recorder.

EXCEPT

That part of the Southwest Quarter of the Southeast Quarter of Section 29, Township 47, Range 26, Aitkin County, Minnesota, lying southeasterly of Minnesota Trunk Highway No. 47.

Aitkin County, Minnesota.
(Abstract)

Surveys/: 29-47-26-Okeson descriptions

SOILS CHARTS FOR BOTH PROPOSED AND ALTERNATE SITES

1 (PROPOSED) SOILS DATA

DEPTH (INCHES)	TEXTURE	MUNSELL COLOR
0-4	Clay loam	10YR 3/2
4-9	clay loam	10YR 3/4
9-13	Sandy Clay loam	10YR 4/4
Mottles 13"		

2 (PROPOSED) SOILS DATA

DEPTH (INCHES)	TEXTURE	MUNSELL COLOR

1 (ALTERNATE) SOILS DATA

DEPTH (INCHES)	TEXTURE	MUNSELL COLOR
0-4	clay loam	10YR 3/2
4-8	clay loam	10YR 3/3
8-14	sandy clay loam	10YR 4/4

2 (ALTERNATE) SOILS DATA

DEPTH (INCHES)	TEXTURE	MUNSELL COLOR

ADDITIONAL SOIL BORINGS MAY BE REQUIRED

MOUND DESIGN WORK SHEET (For Flows up to 1200 gpd)

A. Average Design FLOW

Estimated 450 gpd (see figure A-1)
 or measured _____ x 1.5 (safety factor) = _____ gpd

A-1: Estimated Sewage Flows in Gallons per Day

number of bedrooms	Class I	Class II	Class III	Class IV
2	300	225	180	60%
3	450	300	218	of the
4	600	375	256	values
5	750	450	294	in the
6	900	525	332	Class I,
7	1050	600	370	II, or III
8	1200	675	408	columns.

B. SEPTIC TANK Capacity

1500 gallons (see figure C-1)

C-1: Septic Tank Capacities (in gallons)

Number of Bedrooms	Minimum Liquid Capacity	Liquid capacity with garbage disposal	Liquid capacity with disposal & lift inside
2 or less	750	1125	1500
3 or 4	1000	1500	2000
5 or 6	1500	2250	3000
7, 8 or 9	2000	3000	4000

C. SOILS (refer to site evaluation)

- Depth to restricting layer = 1 feet
- Depth of percolation tests = _____ feet
- Texture clay loam
 Percolation rate _____ mpi
- Soil loading rate .45 gpd/sqft (see figure D-33)
- Percent land slope 2 %

D. ROCK LAYER DIMENSIONS

- Multiply average design flow (A) by 0.83 to obtain required rock layer area.
450 gpd x 0.83 sqft/gpd = 374 sqft
- Determine rock layer width = 0.83 sqft/gpd x linear Loading Rate (LLR)
 0.83 sqft/gpd x _____ gpd/sqft = _____ ft
- Length of rock layer = area ÷ width =
374 sqft (D1) ÷ 10 ft (D2) = 38 ft

Mound LLR

< 120 MPI	≤ 12
≥ 120 MPI	≤ 6

E. ROCK VOLUME

- Multiply rock area (D1) by rock depth of 1 ft to get cubic feet of rock
380 sqft x 1 ft = 380 cuft
- Divide cuft by 27 cuft/cuyd to get cubic yards
380 cuft ÷ 27 cuyd/cuft = 14 cuyd
- Multiply cubic yards by 1.4 to get weight of rock in tons
 _____ cuyd x 1.4 ton/cuyd = 14.63 tons

F. SEWAGE ABSORPTION WIDTH

Absorption width equals absorption ratio (See Figure D-33) times rock layer width (D2)

2.67 x 10 ft = 26.7 ft

D-33: Absorption Width Sizing Table

Percolation Rate in Minutes per Inch (MPI)	Soil Texture	Loading Rate Gallons per day per square foot	Absorption Ratio
Faster than 5	Coarse Sand Medium Sand Loamy Sand Fine Sand	1.20	1.00
6 to 15	Sandy Loam	0.79	1.50
16 to 30	Loam	0.60	2.00
31 to 45	Silt Loam	0.50	2.40
46 to 60	Silt Sandy Clay Loam Silty Clay Loam Clay Loam	0.45	2.67
61 to 120	Silty Clay Sandy Clay Clay	0.24	5.00
Slower than 120*			

*System designed for these soils must be other or performance

G. MOUND SLOPE WIDTH & LENGTH

(landslope greater than 1%)

1. Downslope absorption width = absorption width (F) minus rock layer width (D2)

$26.7 \text{ ft} - 10 \text{ ft} = 16.7 \text{ ft}$

2. Calculate mound size
UPSLOPE

a. Depth of clean sand fill at upslope edge of rock layer = 3 ft minus the distance to restricting layer (C1)

$3 \text{ ft} - 1 \text{ ft} = 2 \text{ ft}$

b. Mound height at the upslope edge of rock layer = depth of clean sand for separation (G2a) at upslope edge plus depth of rock layer (1 ft) plus depth of cover (1 ft)

$2 \text{ ft} + 1 \text{ ft} + 1 \text{ ft} = 4 \text{ ft}$

c. Upslope berm multiplier based on land slope

3.70 (see figure D-34)

d. Upslope width = berm multiplier (G2c) x upslope mound height (G2b):

$3.70 \times 4 \text{ ft} = 14.8 \text{ ft}$

DOWNSLOPE

e. Drop in elevation = rock layer width (D2) x percent landslope (C5) ÷ 100

$10 \text{ ft} \times 2\% \div 100 = 0.2 \text{ ft}$

f. Downslope mound height = depth of clean sand for slope difference (G2e) at downslope rock edge plus the mound height at the upslope edge of rock layer (G2b)

$4.2 \text{ ft} + 0.2 \text{ ft} = 4.2 \text{ ft}$

g. Downslope berm multiplier based on percent land slope

4.35 (see figure D-34)

h. Downslope width = downslope multiplier (G2g) times downslope mound height (G2f)

$4.35 \times 4.2 \text{ ft} = 16.8 \text{ ft}$

i. Select the greater of G1 and G2h as the downslope width:


17 ft

j. Total mound width is the sum of upslope width (G2d) width plus rock layer width (D2) plus downslope width (G2i)

$10 \text{ ft} + 14.8 \text{ ft} + 17 \text{ ft} = 43 \text{ ft}$


k. Total mound length is the sum of upslope width (G2d) plus rock layer length (D3) plus upslope width (G2d)

$14.8 \text{ ft} + 38 \text{ ft} + 16.8 \text{ ft} = 70 \text{ feet}$



D-34: SLOPE MULTIPLIER TABLE

Land Slope, in %	UPSLOPE multipliers for various slope ratios						DOWNSLOPE multipliers for various slope ratios				
	3:1	4:1	5:1	6:1	7:1	8:1	3:1	4:1	5:1	6:1	7:1
0	3.0	4.0	5.0	6.0	7.0	8.0	3.0	4.0	5.0	6.0	7.0
1	2.91	3.85	4.76	5.66	6.54	7.41	3.09	4.17	5.26	6.38	7.53
2	2.83	3.70	4.54	5.36	6.14	6.90	3.19	4.35	5.56	6.82	8.14
3	2.75	3.57	4.35	5.08	5.79	6.45	3.30	4.54	5.88	7.32	8.86
4	2.68	3.45	4.17	4.84	5.46	6.06	3.41	4.76	6.25	7.89	9.72
5	2.61	3.33	4.00	4.62	5.19	5.71	3.53	5.00	6.67	8.57	10.77
6	2.54	3.23	3.85	4.41	4.93	5.41	3.66	5.26	7.14	9.38	12.07
7	2.48	3.12	3.70	4.23	4.70	5.13	3.80	5.56	7.69	10.34	13.73
8	2.42	3.03	3.57	4.05	4.49	4.88	3.95	5.88	8.33	11.54	15.91
9	2.36	2.94	3.45	3.90	4.30	4.65	4.11	6.25	9.09	13.04	18.92
10	2.31	2.86	3.33	3.75	4.12	4.44	4.29	6.67	10.00	15.00	23.33
11	2.26	2.78	3.23	3.61	3.95	4.26	4.48	7.14	11.11	17.65	30.43
12	2.21	2.70	3.12	3.49	3.80	4.08	4.69	7.69	12.50	21.43	43.75



Final Dimensions:
43 x 70

I hereby certify that I have completed this work in accordance with applicable ordinances, rules and laws.

Sau Ann Maschke (signature) 2264 (license #) 5-29-23 (date)

PRESSURE DISTRIBUTION SYSTEM

- Select number of perforated laterals 3
- Select perforation spacing = 3 ft
- Since perforations should not be placed closer than 1 foot to the edge of the rock layer (see diagram), subtract 2 feet from the rock layer length.

$$\frac{38}{\text{Rock layer length}} - 2 \text{ ft} = \underline{36} \text{ ft}$$

- Determine the number of spaces between perforations. Divide the length (3) by perforation spacing (2) and round down to nearest whole number.
Perforation spacing = 36 ft ÷ 3 ft = 12 spaces
- Number of perforations is equal to one plus the number of perforation spaces (4). Check figure E-4 to assure the number of perforations per lateral guarantees <10% discharge variation.

$$\underline{12} \text{ spaces} + 1 = \underline{13} \text{ perforations/lateral}$$

- A. Total number of perforations = perforations per lateral (5) times number of laterals (1)

$$\underline{13} \text{ perfs/lat} \times \underline{3} \text{ lat} = \underline{39} \text{ perforations}$$

- B. Calculate the square footage per perforation. Should be 6-10 sqft/perf. Does not apply to at-grades.
Rock bed area = rock width (ft) x rock length (ft)

$$\underline{10} \text{ ft} \times \underline{38} \text{ ft} = \underline{380} \text{ sqft}$$

$$\text{Square foot per perforation} = \text{Rock bed area} \div \text{number of perfs (6)}$$


$$\underline{380} \text{ sqft} \div \underline{39} \text{ perfs} = \underline{9.74} \text{ sqft/perf}$$

- Determine required flow rate by multiplying the total number of perforations (6A) by flow per perforation (see figure E-6)

$$\underline{39} \text{ perfs} \times \underline{.74} \text{ gpm/perfs} = \underline{29} \text{ gpm}$$

- If laterals are connected to header pipe as shown on upper example, to select minimum required lateral diameter; enter figure E-4 with perforation spacing (2) and number of perforations per lateral (5) Select minimum diameter for perforated lateral = 1.5 inches.

- If perforated lateral system is attached to manifold pipe near the center, lower diagram, perforated lateral length (3) and number of perforations per lateral (5) will be approximately one half of that in step 8. Using these values, select minimum diameter for perforated lateral = _____ inches.



E-4: Maximum allowable number of 1/4-inch perforations per lateral to guarantee <10% discharge variation



perforation spacing (feet)	1 inch	1.25 inch	1.5 inch	2.0 inch
2.5	8	14	18	28
3.0	8	13	17	26
3.3	7	12	16	25
4.0	7	11	15	23
5.0	6	10	14	22

E-6: Perforation Discharge in gpm

head (feet)	perforation diameter (inches)			
	1/8	3/16	7/32	1/4
1.0 ^a	0.18	0.42	0.56	0.74
2.0 ^b	0.26	0.59	0.80	1.04
5.0	0.41	0.94	1.26	1.65

^a Use 1.0 foot for single-family homes.
^b Use 2.0 feet for anything else.

MANIFOLD LOCATED AT END OF PRESSURE DISTRIBUTION SYSTEM



I hereby certify that I have completed this work in accordance with applicable ordinances, rules and laws.

LaurAnn Maschler (signature) 2264 (license #) 5-29-23 (date)

PUMP SELECTION PROCEDURE

1. Determine pump capacity:

A. Gravity distribution

1. Minimum required discharge is 10 gpm
2. Maximum suggested discharge is 45 gpm. For other establishments at least 10% greater than the water supply rate, but no faster than the rate at which effluent will flow out of the distribution device.

B. Pressure distribution

See pressure distribution work sheet

From A or B Selected pump capacity: 29 gpm

2. Determine pump head requirements:

A. Elevation difference between pump and point of discharge?

9 feet

B. Special head requirement? (See Figure at right - Special Head Requirements)

5 feet

C. Calculate Friction loss

1. Select pipe diameter 2 in

2. Enter Figure E-9 with gpm (1A or B) and pipe diameter (C1).

Read friction loss in feet per 100 feet from Figure E-9

Friction Loss = 1.55 ft/100ft of pipe

3. Determine total pipe length from pump discharge to soil treatment discharge point. Estimate by adding 25 percent to pipe length for fitting loss. Total pipe length times 1.25 = equivalent pipe length

45 feet x 1.25 = 56.25 feet


4. Calculate total friction loss by multiplying friction loss (C2) in ft/100 ft by the equivalent pipe length (C3) and divide by 100.

= 1.55 ft/100ft x 56.25 ÷ 100 = .87 ft

D. Total head required is the sum of elevation difference (A), special head requirements (B), and total friction loss (C4)

14 ft + .87 ft + .87 ft =

Total head: 13.87 feet



Special Head Requirements	
Gravity Distribution	0 ft
Pressure Distribution	5 ft

E-9: Friction Loss in Plastic Pipe Per 100 feet			
flow rate gpm	nominal pipe diameter		
	1.5"	2"	3"
20	2.47	0.73	0.11
25	3.73	1.11	0.16
30	5.23	1.55	0.23
35	6.96	2.06	0.30
40	8.91	2.64	0.39
45	11.07	3.28	0.48
50	13.46	3.99	0.58
55		4.76	0.70
60		5.60	0.82
65		6.48	0.95
70		7.44	1.09

3. Pump selection


A pump must be selected to deliver at least 29 gpm (1A or B) with at least 14 feet of total head (2D)

I hereby certify that I have completed this work in accordance with applicable ordinances, rules and laws.

Lou Ann Maschke (signature) 2264 (license #) 5-29-23 (date)

DATE: 5-29-23

MAP DRAWN TO SCALE WITH A NORTH ARROW



CHECK OFF LIST-HAVE ALL OF THE FOLLOWING BEEN DRAWN ON THE MAP??

- SHOW EXISTING OR PROPOSED
- WATER WELLS WITHIN 100 FT OF TREATMENT AREAS
 - PRESSURE WATER LINES WITHIN 10 FT OF TREATMENT AREAS
 - STRUCTURES
 - ALL SOIL TREATMENT AREAS
 - HORIZONTAL AND VERTICAL REFERENCE
 - POINT OF SOIL BORINGS
 - LOT EASEMENTS
 - DISTURBED/COMPACTED AREAS
 - SITE PROTECTION-LATHE AND RIBBON EVERY 15 FT
 - ACCESS ROUTE FOR TANK MAINTENANCE
 - REQUIRED SETBACKS
 - STRUCTURES
 - OHWL
 - LOT IMPROVEMENTS
 - ALL ISTS COMPONENTS
 - DIRECTION OF SLOPE
 - ALL LOT DIMENSIONS
 - PROPERTY LINES

INDICATE ELEVATIONS

- BENCHMARK 100' top tank ?
- ELEVATION OF SEWER LINE @ HOUSE ?
- ELEVATION @ TANK INLET 98'
- ELEVATION @ BOTTOM OF ROCK LAYER 104'
- ELEVATION @ BOTTOM OF BORING OR RESTRICTIVE LAYER 99'
- ELEVATION OF PUMP 94'
- ELEVATION OF DISTRIBUTION DEVICE

DESIGNER SIGNATURE Saul Ann Mascopler

LICENSE# 2764

DATE 5-29-23

Subsurface Sewage Treatment System Management Plan

Property Owner: Joe Baker & Virginia O'Keefe Phone: _____ Date: 5-29-23
Mailing Address: _____ City: _____ Zip: _____
Site Address: 38588 Hwy 47 City: Aitkin Zip: 56431

This management plan will identify the operation and maintenance activities necessary to ensure long-term performance of your septic system. Some of these activities must be performed by you, the homeowner. Other tasks must be performed by a licensed septic service provider.

System Designer: check every _____ months.
Local Government: check every _____ months.
State Requirement: check every 36 months.

My System needs to be checked every 36 months.

Homeowner Management Tasks

- Leaks* – Check (look, listen) for leaks in toilets and dripping faucets. Repair leaks promptly.
- Surfacing sewage* – Regularly check for wet or spongy soil around your soil treatment area.
- Effluent filter* – *Inspect and clean twice a year or more.*
- Alarms* – Alarm signals when there is a problem. Contact a service provider any time an alarm signals.
- Event counter or water meter* – Record your water use.
-recommend meter readings be conducted (circle one: DAILY WEEKLY MONTHLY)

Professional Management Tasks

- Check to make sure tank is not leaking
- Check and clean the in-tank effluent filter
- Check the sludge/scum layer levels in all septic tanks
- Recommend if tank should be pumped
- Check inlet and outlet baffles
- Check the drainfield effluent levels in the rock layer
- Check the pump and alarm system functions
- Check wiring for corrosion and function
- Check dissolved oxygen and effluent temperature in tank
- Provide homeowner with list of results and any action to be taken
- Flush and clean laterals if cleanouts exist

"I understand it is my responsibility to properly operate and maintain the sewage treatment system on this property, utilizing the Management Plan. If requirements in the Management Plan are not met, I will promptly notify the permitting authority and take necessary corrective actions. If I have a new system, I agree to adequately protect the reserve area for future use as a soil treatment system."

Property Owner Signature: Joe Baker Date: 5-29-23
Designer Signature: Southern Maschler Date: 5-29-23

See Reverse Side for Management Log