Subsurface Sewage Treatment System Management Plan

Property Owner: Larry Kruckeberg	rry Kruckeberg Phone:		Date: 6/22/2020		
Mailing Address: 405 E Front St.	City: Cla	remont MN	Zip: 55924 Zip: 56469		
Site Address: 49052 372nd Pl.	City: Pali	sade MN			
Local Government: check every 36	e activities must be povider months months.	erformed by you, the h	eds to be checked		
State Requirement: check every 36					
(State requirements are based on MN Rules Chapter 7080.245) Homeowner Management Tasks	50, Subp. 2 & 3)				
Leaks – Check (look, listen) for lea Surfacing sewage – Regularly chec Effluent filter – Inspect and clean t Owner> Alarms – Alarm signals when there Event counter or water meter – Re -recommend meter reading	ck for wet or spongy twice a year or more e is a problem. Conta ecord your water use	soil around your soil tre act a service provider ar .	eatment area.		
Professional Management Tasks ✓ Check to make sure tank i	s not leaking				
Check and clean the in-tar Check the sludge/scum law Recommend if tank should	yer levels in all septi d be pumped	c tanks			
Check inlet and outlet baf Check the drainfield efflue		layer			
☑ Check the pump and alarr	•				
Check wiring for corrosion					
☐ Check dissolved oxygen a	•				
Provide homeowner with		y action to be taken			
☐ Flush and clean laterals if	cleanouts exist				
"I understand it is my responsibility to properly operate Management Plan. If requirements in the Management necessary corrective actions. If I have a new system, I a system."	t Plan are not met, I w	Il promptly notify the perr	mitting authority and take		
Property Owner Signature:		Date:			
Designer Signature: Oeff Br	ummer	Date:	6/22/2020		

See Reverse Side for Management Log

Maintenance Log

Activity		Date Accomplished				
Check frequently:						
Leaks: check for plumbing leaks						
Soil treatment area check for surfacing						
Lint filter: check, clean if needed						
Effluent screen: if owner-maintained						
Water usage rate (monitor frequency)						
Check annually:						
Caps: inspect, replace if needed						
Sludge & Scum/Pump						
Inlet & Outlet baffles						
Drainfield effluent leaks						
Pump, alarm, wiring						
Flush & clean laterals if cleanouts exists						
Other:						
Other:						
Notes: Check alarm at least once a year. Pump Tank Mow Mound Area at least once a year to keep brush a				rs		
No Traffic on mound area, No Snowmobiles, No ATV's	s, No Parkir	ng.				
Mitigation/corrective action plan:						