Subsurface Sewage Treatment System Management Plan

Property Owner: Janet Sanderson Mailing Address: 45807 295th St. Site Address: 45807 295th St.		Phone: 6	12-723-1960	Date: 5/7/2023		
		City: Aitkin MN 56431				
				Zip:		
performance of your sept must be performed by a l	ill identify the operation and mai tic system. Some of these activiti- icensed septic service provider.	es must be p		_		
Local Government: che	s every 36 months. s every 36 months. s every 36 months.		My System nee every <u>36</u>	ds to be checked months.		
	on MN Rules Chapter 7080.2450, Subp	2 & 3)				
Homeowner Mai	nagement Tasks					
Owner> Effluent f Owner> Alarms – Event cou	theck (look, listen) for leaks in toing sewage – Regularly check for well in the list of t	et or spongy year or more. oblem. Conta our water use	soil around your soil trea act a service provider any	atment area.		
Funderstand it is my respo	Check to make sure tank is not lead theck and clean the in-tank efflue check the sludge/scum layer leve decommend if tank should be pure check inlet and outlet baffles check the drainfield effluent level check the pump and alarm system check wiring for corrosion and fure check dissolved oxygen and efflue trovide homeowner with list of real lush and clean laterals if cleanous insibility to properly operate and management.	ent filter Is in all seption Is in the rock In functions Inction Incti	layer ture in tank y action to be taken rage treatment system on t			
necessary corrective actions system."	ements in the Management Plan are	adequately pro	otect the reserve area for fu	uture use as a soil treatment		
Property Owner Signatur			Date: _			
Designer Signature	Jeff Brummer		Date:	5/7/2023		

Maintenance Log

Activity		Date Accomplished						
Check frequently:								
Leaks: check for plumbing leaks								
Soil treatment area check for surfacing								
Lint filter: check, clean if needed								
Effluent screen: if owner-maintained								
Water usage rate (monitor frequency)								
Check annually:								
Caps: inspect, replace if needed								
Sludge & Scum/Pump								
Inlet & Outlet baffles								
Drainfield effluent leaks								
Pump, alarm, wiring								
Flush & clean laterals if cleanouts exists								
Other:								
Other:								
Notes: Check alarm at least once a year. Pump Tank Mow Mound Area at least once a year to keep brush a				rs				
No Traffic on mound area, No Snowmobiles, No ATV's	s, No Parkir	ng.						
Mitigation/corrective action plan:								