Holding Tank

Subsurface Sewage Treatment System Management Plan

Property Owner: Tommy Wynn Mailing Address: 29849 400th Ave.			Phone: 9	19-669-4373	Date: 7/17/2024 Zip: Zip:		
			City:				
				in MN 56431			
performance of must be perform	your se	ptic system. Some	of these acti ervice provide	vities must be per.	tivities necessary to ens performed by you, the ho	_	
System Designer: Local Government: State Requirement:		heck every <u>12</u>		months. months. months.		eds to be checked months.	
(State requirement	s are base	ed on MN Rules Chapte	er 7080.2450, Su	ıbp. 2 & 3)			
Homeo	wner M	anagement Tasks					
Owner>	Surfacii		arly check fo	r wet or spongy	ping faucets. Repair leal soil around your soil tre		
Owner>	Alarms	 Alarm signals w 	hen there is a	problem. Cont	act a service provider an	y time an alarm signals.	
Owner>	Event c	ounter or water m	<i>eter</i> – Record	d your water use	2.		
		-recommend met	er readings b	e conducted (<i>ci</i>	rcle one: <u>DAILY</u> <u>WE</u>	EEKLY MONTHLY)	
Protess		anagement Tasks					
		Check to make su		_			
	. /	Check and clean t					
	Y	Check the sludge			c tanks		
	V ₁	Recommend if ta		pumped			
		Check inlet and o	utlet baffles				
Check the drainfield effluent levels in t					alayer		
		Check the pump					
	lacksquare	Check wiring for	corrosion and	function			
		Check dissolved o	xygen and ef	fluent tempera	ture in tank		
	Y				y action to be taken		
		Flush and clean la			•		
Management Pla	n. If requ	irements in the Ma	nagement Plar	are not met, I w	vage treatment system on ill promptly notify the perrotect the reserve area for f		
Property Owner	r Signatı	ıre:			Date:		
Designer Signat	iire.	Oo.LL	Brumm	er	Date:	7/17/2024	

See Reverse Side for Management Log

Maintenance Log

Activity		Date Accomplished								
Check frequently:										
Leaks: check for plumbing leaks										
Soil treatment area check for surfacing										
Lint filter: check, clean if needed										
Effluent screen: if owner-maintained										
Water usage rate (monitor frequency)										
Check annually:	·									
Caps: inspect, replace if needed										
Sludge & Scum/Pump										
Inlet & Outlet baffles										
Drainfield effluent leaks										
Pump, alarm, wiring										
Flush & clean laterals if cleanouts exists										
Other:										
Other:										
Notos: Check alarm once a vear										
Notes: Check alarm once a year										
Holding Tank, pump when full, pumper should check for leaks	s or cracks									
Mitigation/corrective action plan:										
							,			
									—	

P:\PZSHARE\Forms\SSTS Management Plan.docx